



New Product Bulletin #16

The ZT3000A Lightweight R/A Positive Feed Drill



The ZT3000A New Right Angle Positive-Feed Drillmotor

- Plenty of power in a small package - 1.5 hp motor yet only weighs 7 lbs.!
- Drilling diameter capacity of 1" Alum./ .750" Steel/ .625" Titanium
- Standard spindle is coolant-ready and comes with 9/16"-18 internal thread. Other thread sizes available.
- Simple two-gear replacement to change feed rate – dot markings on gears prevents mismatching gears!
- Has 1"-20 nose attachment thread that accepts existing 15QDA-RA noses used on 140QGDA/932Q/952Q/962Q tools.
- Simple nose indexer lever allows nosepiece orientation in 30° increments.
- Fully automatic air logic system allows pull to start/ push to stop; tool can be started in either feed or retract mode; auto retract and shutoff at the end of drilling cycle.
- Air hose can be attached to one of three inlet port locations.

Specifications

Model Number	RPM Options	Feed Rates (IPR)	Power	Weight	Stroke	Air Volume	Tool Nose Radius
ZT3000A	200; 300; 450; 650; 1800; 2800; 4000	.001"; .002"; .003"; .004"; .005"; .006"; .007"; .008"	1.5 hp. / 455 in-lbs stall torque	7 lbs.	.375" Min. / Unlimited max. stroke	44-52 CFM @ 90 psi.	.780"

[Full One-Year Parts & Workmanship Warranty on this tool!!](#)

[Call for further information or a demo today!](#)

