



CP Rivet Hammers



CP4444-RUSAB



CP4447-RUVAB

Model Number	"X" reference	Blows/min.	Stroke	Shank dia.	Max. Dia. Alum.	Max. Dia. Steel	Length	Weight
CP4444-RURAB	2X	2580	2"	.401"	1/8"	3/32"	6.7"	2.2 lbs.
CP4444-RUSAB	3X	2160	3"	.401"	3/16"	5/32"	7.3"	2.3 lbs.
CP4444-RUTAB	4X	1740	4"	.401"	1/4"	3/16"	8.3"	2.75 lbs.
CP4447-RUSAB	5X	1560	2.68"	.498"	1/4"	3/16"	8.9"	4.7 lbs.
CP4447-RUTAB	9XB	1700	3.875"	.498"	5/16"	1/4"	9.9"	5.1 lbs.
CP4447-RUVAB	7XB	900	5.813"	.498"	3/8"	5/16"	11.9"	9 lbs.



CP4450-3 Vibration Reduced Rivet Hammer

Model Number	"X" reference	Blows/min.	Stroke	Shank dia.	Max. Dia. Alum.	Max. Dia. Steel	Length	Weight
CP4450-2	2X	2508	2"	.401"	1/8"	3/32"	8.4"	2.7 lbs.
CP4450-3	3X	2160	3"	.401"	3/16"	5/32"	8.9"	2.8 lbs.
CP4450-4	4X	1740	4"	.401"	1/4"	3/16"	9.9"	3.2 lbs.



USI Rivet Hammers



US3X

Model Number	Blows/min.	Stroke	Shank dia.	Max. Dia. Alum.	Length	Weight
US1X	2580	1.5"	.401"	1/8"	5.687"	2 lbs.
US2X	2580	2.25"	.401"	1/8"	6.687"	2.3 lbs.
US3X	2160	2.875"	.401"	3/16"	7.312"	2.3 lbs.
US4X	1740	3.062"	.401"	1/4"	8.5"	2.8 lbs.
US5X	1560	2.687"	.498"	1/4"	9.25"	5 lbs.
US7X	900	5.813"	.498"	3/8"	11.5"	6.1 lbs.
US9X	1140	3.875"	.498"	5/16"	10"	5.3 lbs.



US200B "Jiffy-Style"
Rivet Hammer

Model Number	Blows/min.	Stroke	Shank dia.	Max. Dia. Alum.	Length	Weight
US100B*	2850	1.875"	.401"	5/32"	3.625"	2.1 lbs.
US200B*	2700	2.25"	.401"	3/16"	5.375"	3.1 lbs.

*Special short shank .401 rivet sets required for use with this tool!



US3R Recoilless Rivet Hammer

Model Number	Blows/min.	Stroke	Shank dia.	Max. Dia. Alum.	Max. Dia. Steel	Length	Weight
US2R	2250	2"	.401"	5/32"	1/8"	6.875"	2.8 lbs.
US3R	1900	3"	.401"	3/16"	5/32"	7.875"	3 lbs.
US4R	1650	4"	.401"	7/32"	3/16"	8.875"	3.3 lbs.
US5R	1400	5"	.401"	1/4"	3/16"	9.875"	3.5 lbs.