



**Tab Shear/ Saw Blades & Accessories**



**750 Tab Shear**

**Model 750 Tab Shear**

You can efficiently shear router tabs from aluminum, steel, titanium, and stainless steels or perform similar shearing and trimming operations with this powerful tool.

- Shearing Capacity: 1/8" Alum. / 1/16" Steel
- Max. throat opening: 1/8" x 3"
- Shearing force: 4,200 lbs.
- Weighs 7 lbs.
- Shear blades may be re-sharpened or rotated to new edge.



**1/4" Arbor Saw Blades**

Part Number	Dia.	Type	Max Cut Depth & Width	Max RPM	Recommended Mat'l
14-1875	1-1/4"	HSS 22T	3/32" x 1/16"	12,000	Alum., Laminate Plastic, Wood
14-0930	1-1/4"	HSS 44T	3/32" x 1/16"	12,000	Alum., Laminate Plastic, Wood
14-1895	1-1/2"	HSS 22T	7/32" x 1/16"	12,000	Alum., Laminate Plastic, Wood
14-1890	2"	HSS 22T	7/16" x 1/16"	12,000	Alum., Laminate Plastic, Wood
14-1891	2"	HSS 44T	7/16" x 1/16"	12,000	Alum., Laminate Plastic, Wood
14-1892	2"	HSS 60T	7/16" x 1/16"	12,000	Alum., Laminate Plastic, Wood
14-1396	1-1/2"	Carbide Chip 36/80 Grit	7/32" x 3/32"	20,000	Fiberglass, Rubber, non-metallic materials
14-1395	2"	Carbide Chip 36/80 Grit	7/16" x 3/32"	20,000	Fiberglass, Rubber, non-metallic materials
14-1398	1-1/2"	Diamond Chip 40/60 Grit	7/32" x 5/64"	20,000	Fiberglass, Rubber, non-metallic materials
14-1400	2"	Diamond Chip 40/60 Grit	7/16" x 5/64"	20,000	Fiberglass, Rubber, non-metallic materials



**1AM1141-51K**

**Sioux Sealant Removal Kits for Aircraft Maintenance**

These kits were developed specifically for aircraft sealant removal applications. There are 10 ea. 3M brand sealant removal cutters included in each kit along with a 90 degree angle drill and an additional 45 degree drill attachment. The cutters thread directly into the female thread in the 90 or 45 degree drillmotor without an adapter. The sealant removal kits partially eliminate a need for the use of chemical solvents, which raise safety, health, and environmental issues not to mention saving the messy clean-up.